

The Lobster brand tools has 120 years of history and we, at LOBTEX, presently specialize in large varieties of tools to meet the needs of professional and home use. Lobster rivet tool as the world leader in rivet tool performance, engineering and value. That's why no other rivet tool manufacturer in the world matches the design innovation, product versatility and craftsmanship you'll find with lobster rivet Tools.

FASTENER & INDUSTRIAL TOOLS



Lobster rivet tools offers the most comprehensive line of blind rivet and rivet nut tools available anywhere. Lobster's innovative tools are engineered to satisfy the ergonomic challenges, mechanical precision, durability and increased productivity that today's industry demands. In fact, lobster rivet tools are certified to ISO 9001 - the world's highest quality standard - ensuring that the entire engineering and production process meets the highest international standards. Lobster rivet tools deliver value where it matters most - on the job. That's why productivity is enhanced when lobster rivet tools become a part of your production system. Performance. Engineering. Value. With lobster rivet tools you can feel the difference.



Durable & Portable

- * It is the air riveter of the off-the-shelf item.
- * It is the long seller machine which was excellent about the durability.

Model	Riveting Capacity	Traction Power	Stroke	Working Air Pressure	Air Consumption	Tool Dimensions	Nosepiece	Frame Head	Jaws	Auxiliary Kit
AR-01M Medium	For setting blind rivets up to 3/16" (4.8mm) in steel	1760 lbs (800kg) (7849N)	0.552" (14.0mm)	74-85 p.s.i. (5-6kg/cm2)	0.053 cu ft (1.5 liter/rivet)	H 10.669" (271mm) L 8.858" (225mm) Wt 3.125 lbs (143kg)	Standard 3/32-3/16" (2.4-4.8mm) L 1.0256" (6.5mm) D 1.0295" (7.5mm)	L 2.283" (58mm) D 0.906" (23mm)	M	4 Nosepieces 3/32" (2.4mm) 1/8" (3.2mm) 5/32" (4.0mm) 3/16" (4.8mm)
AR-01H Heavy Duty	For setting blind rivets up to 1/4" (6.4mm) in all materials	2750 lbs (1250kg) (12259N)	0.630" (16.0mm)	85-92 p.s.i. (6-6.5kg/cm2)	0.102 cu ft (2.9 liter/rivet)	H 12.28" (312mm) L 10.12" (257mm) Wt 4.625 lbs (2.10kg)	Standard 3/32-3/16" (2.4-4.8mm) 1/4" (6.4mm) L 1.0295" (7.5mm) D 1.0472" (12mm)	L 2.285" (72.5mm) D 0.984" (25mm)	M H	5 Nosepieces 3/32" (2.4mm) 1/8" (3.2mm) 5/32" (4.0mm) 3/16" (4.8mm) 1/4" (6.4mm) H jaws set jaw pusher and jaw casehead for 1/4" rivets