



## Slam Latches

## Snap-in Magnetic Catch With Round Housing




## southco





- Pull the door to open
- Push the door closed to latch
- Two sizes available
- Polypropylene construction
- Single hole snap-in installation
- Housing is UL94-HB rated
- Black finish
- \* Screw mounted and adhesive backed striked are available for non-ferrous application




Product Strength Guidelines								
	Average	Standard						
Size	Breakaway Force	Deviation						
Small	14 N (0 1 lba)	0.0 N (0.040 lba)						
(400 series)	14 N (3.1 lbs.)	2.2 N (0.049 lbs.)						
Large	40 N (11 lbs )	6.4 N (1.4 lbs.)						
(600 series)	49 N (11 lbs.)							

## <u>INSTALLATION</u>

1.


Punch rectangular slot



SIZE	ØН		
Small (400 Series)	14,3 +0,1 -0,0		
Large (600 Series)	22,3 +0,1 -0,0		

2

Snap catch into hole



Cino	Dimensions						Frame Thickness		Part Number	Rated Load
Size	ØΑ	В	С	D	ØΕ	F	Min	Max	Part Number	haleu Loau
Small						0.8	0.5	2	02-20-411-10	
1	16	8	21.4	0.8	14.2	2.3	2	3.5	02-20-412-10	24 N (5.5 lbs)
(400 series)						3.8	3.5	5	02-20-413-10	
						0.5	0.5	2	02-20-611-10	
Large	24.5	1.2	33.5	0.8	22.1	2	2	3.5	02-20-612-10	58 N (13 lbs)
(600 Series)						3.5	3.5	5	02-20-613-10	]